
sphinx-revealjs Documentation

Release 1.5.3

Kazuya Takei

Jun 01, 2022

CONTENTS

1 Basic Features	3
2 Demo	5
3 Concept and motivation	7
4 Contents	9
4.1 Setup	9
4.2 Upgrading guide	10
4.3 Configurations	11
4.4 Directives	15
4.5 Using examples	17
4.6 Changelog	18
5 Licenses	29
6 Indices and tables	31
Index	33

`sphinx-revealjs` is Sphinx extension to generate Reveal.js presentation documents from **standard** reStructuredText.

**CHAPTER
ONE**

BASIC FEATURES

- Nested sections
- Speaker note
- Syntax highlight for Reveal.js (not used pygments)
- Customize slides and sections by conf.py or source reST

**CHAPTER
TWO**

DEMO

- Source: Sphinx document
- Created: Reveal.js presentation

```
=====
sphinx-revealjs
=====

.. revealjs_slide::

{
    controls: true,
    progress: true,
    history: true,
    center: true,
    transition: "slide",
    dependencies: [
        { src: "{{ pathto('_static/revealjs/plugin/notes/notes.js', 1) }}", async: true },
        { src: "{{ pathto('_static/revealjs/plugin/highlight/highlight.js', 1) }}", async: true, callback: function() {
    }
}
}

:Based version: 0.9.0
:Released: 2019-12-22

Overview
=====

What is this?
-----

Sphinx extension to build Revealjs presentation

Features
-----

.. This is reST comment. Render into speaker note section

* Convert sections from reStructuredText directly
* Select theme from default themes

Convert sections from reStructuredText directly
=====

Adjust section structure
```

sphinx-revealjs

Based version:
0.9.0

Released:
2019-12-22

**CHAPTER
THREE**

CONCEPT AND MOTIVATION

Goal of this library is to provide presentation platform for self-branding of engineer using Sphinx. Using static site hosting service, you can show own presentations to anyone.

Core motivation is that I want to play presentation by this library.

CONTENTS

4.1 Setup

4.1.1 Requirements

`sphinx-revealjs` requires Python 3.6+ and Sphinx.

Current development environment

- Python: 3.9
- Sphinx: 3.5.4

4.1.2 Installation

You can install `sphinx-revealjs` from PyPI.

```
$ pip install sphinx-revealjs
```

`sphinx-revealjs` specify Sphinx and docutils expressly as dependencies. You get Sphinx by this command only.

4.1.3 Configuration

`sphinx-revealjs` does not provide `revealjs` builder instead of `html` builder. To use builder, edit your `conf.py`.

```
extensions = [  
    "sphinx_revealjs",  
]
```

if you want to configure more, edit `conf.py` with seeing [*Configurations*](#).

4.1.4 Build

Run `make` command to build presentations. Files are generated to `revealjs` folder.

```
$ make revealjs
```

You can generate all pages as `index.html` to use `dirrevealjs`.

```
make dirrevealjs
```

4.2 Upgrading guide

4.2.1 To 1.x from 0.x

From version 1.x, this bundle Reveal.js 4.x, and implement for it. Due it, documentations for old version does not work to build correctly.

You have to lock version, or migrate source for next version.

revealjs_script_plugins

Reveal.js 4.x has big changes for usage of plugins from 3.x.

`sphinx-revealjs` is also adjust for this changes, and need update `revealjs_script_plugins`.

```
revealjs_script_plugins = [
    {
        "name": "RevealNotes",
        "src": "revealjs4/plugin/notes/notes.js",
        - "src": "revealjs/plugin/notes/notes.js",
    },
    {
        "name": "RevealHighlight",
        "src": "revealjs4/plugin/highlight/highlight.js",
        - "src": "revealjs/plugin/highlight/highlight.js",
        - "options": """
            {async: true, callback: function() { hljs.initHighlightingOnLoad(); } }
        """
    },
]
```

- Changed structure from src and options to src and name.
 - For 4.x, to use plugin for core,
add class name of it not source path,
and need to preload source by `script` tag.
 - Class name is defined in plugin source.
You need find from source or ref documents (official plugin only)
 - In adding, does not accept options for plugins.

MORE: See [Using Plugins from Reveal.js document](#)

revealjs_css_files

If you use highlight plugin and specify bundled stylesheet file, change path of stylesheet. Style files is migrated to highlight plugin folder.

- Before: revealjs/lib/css/zenburn.css
- After: revealjs4/plugin/highlight

4.3 Configurations

sphinx-revealjs can build multiple presentations. You can configure in `conf.py` for all presentations.

4.3.1 Basic configurations

revealjs_static_path

Type
list

Default
[] (empty)

Example
["_static"]

List of static files directory (same as `html_static_path`)

revealjs_js_files

Type
list

Default
[] (empty)

Example
["custom.js"]

List of using custom js (same as `html_js_files`).

When you want to use JS that does not related revealjs, can use this.

revealjs_css_files

Type
list

Default
[] (empty)

Example
["custom.css"]

List of using custom css (same as `html_css_files`).

If you want to customize presentation by CSS, write external css and use it.

4.3.2 Style Configurations

revealjs_style_theme

Type
str

Default
black

Example
moon, custom.css

Theme name of stylesheet for Reveal.js.

- If value does not have suffix .css,
use bundled Reveal.js theme(included revealjs/css/theme).

4.3.3 Presentation Configurations

revealjs_use_section_ids

Type
boolean

Default
False

If this is set True, inject id attribute into section element (parent of headerings). This means that change format of internal links (default is numbering style).

revealjs_script_files

Type
List[str]

Default
[]

Example
["presentation.js"]

List of sources that render as script tags.

There is bundled Reveal.js script at revealjs/js/reveal.js.

Example:

```
<div>
    <!-- Presentation body -->
</div>
<!-- here!! -->
<script src="_static/revealjs/js/revealjs.js"></script>
<script src="_static/presentation.js"></script>
```

revealjs_script_conf

Type
str or dict

Default

None

Configuration of Reveal.js presentation. This value is used as options of `Reveal.initialize` in output files.

- If value is string type, handle as raw javascript code.
- If value is dict object, convert to json string at internal.

Example 1: case of str

```
revealjs_script_conf = """
{
    controls: false,
    transition: 'zoom',
}
"""
```

```
<div>
    <!-- Presentation body -->
</div>
<script src="_static/revealjs/js/revealjs.js"></script>
<!-- here!! -->
<script>
    let revealjsConfig = {};
    revealjsConfig = Object.assign(revealjsConfig, {
        controls: false,
        transition: 'zoom',
    });
    revealjs.initialize(revealjsConfig);
</script>
```

Example 2: case of dict

```
revealjs_script_conf = {
    "controls": False,
    "transition": "zoom",
}
```

```
<div>
    <!-- Presentation body -->
</div>
<script src="_static/revealjs/js/revealjs.js"></script>
<!-- here!! -->
<script>
    let revealjsConfig = {};
    revealjsConfig = Object.assign(revealjsConfig, JSON.parse('{"controls": false,
    "transition": "zoom"}'));
    revealjs.initialize(revealjsConfig);
</script>
```

example 1 and 2 are behaving same.

revealjs_script_plugins**Type**

List[Dict]

Default

[]

List of plugin configurations. If this value is set, render `script` tag after source `script` tags.

There are bundled Reveal.js plugins at `revealjs/plugin`.

Example:

```
revealjs_script_plugins = [
    {
        "src": "revealjs4/plugin/highlight/highlight.js",
        "name": "RevealHighlight",
    },
]
```

```
<div>
    <!-- Presentation body -->
</div>
<script src="_static/revealjs/js/revealjs.js"></script>
<script src="_static/revealjs/plugin/highlight/highlight.js"></script>
<!-- here!! -->
<script>
    let revealjsConfig = {};
    revealjsConfig.plugins = [RevealHighlight,];
    revealjs.initialize(revealjsConfig);
</script>
```

4.3.4 Font configurations

Note: These configurations will be dropped when version 2.x.

You can use raw CSS or `googlefonts-markup` instead of these.

`revealjs_google_fonts`

Type

dict

Default

[]

Example

[]

List of using fonts from [Google Fonts](#). If this value is set, render `link` and `style` tags into html.

`revealjs_generic_font`

Type

str

Default

sans-serif

Example

serif, monospace

If you use `revealjs_google_fonts`, set last of `font-family` style.

4.4 Directives

`sphinx-revealjs` provides some directives to customize presence and behaviors.

4.4.1 For customize presentation

Sphinx can manage multiple documents, so that `sphinx-revealjs` can build multiple presentation slides.

If you want to configure one presentation from some, use this directive into your source.

.. revealjs-slide::

Write `revealjs-slide` directive on directly below of title header.

Note: Directive based customize has options less than conf based because implementation restrict.

:theme: (string)

Override `revealjs_style_theme`.

:google_font: (string)

Override `revealjs_google_fonts`, but it can specify only one.

:conf: (JSON-string or no-value)

Override `revealjs_script_conf`, but single line only.

Usage:

```
Presentation title
=====
```

```
.. revealjs-slide::
```

```
  :theme: moon
```

```
Section
-----
```

```
Content
```

4.4.2 For customize sections

If you want to change behavior of sections, use these directives.

.. revealjs-section::

To change behavior per section, write directive per section.

:data-XXX:

This directive can accept attribute as same as Reveal.js section tags.

Usage:

Write `revealjs-slide` directive on directly below of section title header.

```
Title  
=====
```



```
Section  
-----
```



```
.. revealjs-section::  
:data-background-color: #009900
```

.. revealjs_section::

Alias of revealjs-section for backward compatibility.

Note: This will be dropped when version 2.x

.. revealjs-break::

If you want to transition section with keeping title, revealjs-break can use.

Usage:

Write revealjs-break to point of want to split section.

```
Title  
=====
```



```
Section  
-----
```



```
Content 1
```



```
.. revealjs-break::
```



```
Content 2(next slide)
```

:data-XXX:

It accepts attributes as same as revealjs-section.

:notitle:

If it is set in directive, next section page does not display title.

.. revealjs_break::

Alias of revealjs-break For backward compatibility.

Note: This will be dropped when version 2.x

4.4.3 For interactive contents

.. revealjs-code-block::

This is extends of `code-block` direcive for presentation.

If you want to use `data-line-number` attributes in code-block.

:data-line-numbers: (string or no value)

Code highlighting pattern. See [Reveal.js](#) document

Example:

```
.. revealjs-code-block:: python
  :data-line-numbers: 1

  def hello():
    print("world")
```

.. revealjs-fragments::

Note: There are cases not working regular.

Inject `fragment` attribute into objects. Referer to “Fragments” from Reveal.js

Example:

Write block as directive that you want to present as fragments.

```
.. revealjs-fragments::
```

```
* First
* Second
* Third
```

See [demo](#)

.. revealjs_fragments::

Alias of `revealjs-fragments` for backward compatibility.

Note: This will be dropped when version 2.x

4.5 Using examples

4.5.1 List

Customizing design simply

When using bundled theme, you can customze design by adding custom CSS.

Example: Disable transform style in header text

Some of reveal.js bundled themes (ex: `black`) set uppercase in `text-transform` of heading texts. You can add extra custom CSS to use other settings.

Source

Listing 1: conf.py

```
revealjs_css_files = [
    "revealjs4/plugin/highlight/zenburn.css",
    "custom.css",
]
```

Listing 2: custom.css

```
.reveal h1, .reveal h2, .reveal h3, .reveal h4, .reveal h5, .reveal h6 {
    text-transform: none;
}
```

4.6 Changelog

4.6.1 ver 1.5.3

date
2022-06-02

base
Reveal.js 4.3.1

Fixes

- All nodes for `sphinx-revealjs` does not write anything when none revealjs builder works.

4.6.2 ver 1.5.2

date
2022-04-29

base
Reveal.js 4.3.1

Fixes

- Work `revealjs-break` directive in `dirrevealjs` builder (#109)
- Inherit behavior of any nodes from `html` builder to `dirrevealjs` builder (#108)

Deprecated

Mark as deprecated(logging.warning) to drop at version 2.x (updated from v1.5.0)

- Snake-cased directive (`revealjs_slide`, `revealjs_section` and `revealjs_break`)
- CSS Font configurations (`revealjs_google_fonts` and `revealjs_generic_font`)
- Passing values from `html_js_files` to `revealjs_js_files`

4.6.3 ver 1.5.1

date

2022-04-21

base

Reveal.js 4.3.1

Fixes

- Add `role="main"` into `page.html` for searching by Sphinx (#102)

Misc

- Add documentation link into metadata (PyPI)

4.6.4 ver 1.5.0

date

2022-04-11

base

Reveal.js 4.3.1

Features

- Add `dirrevealjs` builder to generate all pages as `index.html`

Deprecated

Mark as deprecated(logging.info) to drop at version 2.x

- Snake-cased directive (`revealjs_slide`, `revealjs_section` and `revealjs_break`)
- CSS Font configurations (`revealjs_google_fonts` and `revealjs_generic_font`)
- Passing values from `html_js_files` to `revealjs_js_files`
- Full-support for Python 3.6.x

4.6.5 ver 1.4.6

date
2022-03-26

base
Reveal.js 4.3.1 (updated)

(Only update reveal.js)

4.6.6 ver 1.4.5

date
2022-03-06

base
Reveal.js 4.3.0 (updated)

(Only update reveal.js)

4.6.7 ver 1.4.4

date
2021-12-12

base
Reveal.js 4.2.1 (updated)

(Only update reveal.js)

4.6.8 ver 1.4.3

Date
2021-11-20

Reveal.js
v4.2.0

(None updates for features)

Extra

- Update classifiers of PyPI
 - Fix key of license
 - Add other keys

4.6.9 ver 1.4.2

Date

2021-11-20

Reveal.js

v4.2.0

(None updates for features)

Extra

- Update test matrix of GitHub Actions to confirm that this supports python 3.10
- Update classifiers of PyPI because test cases passed under Python 3.10 and Sphinx 4.x

4.6.10 ver 1.4.1

Date

2021-11-16

Reveal.js

v4.2.0 (updated)

Fixes

- Replace reveal.js to use right bundle version.

4.6.11 ver 1.4.0

Date

2021-11-13

Reveal.js

v4.2.0 (updated)

New features

- Add `revealjs_js_files` for `conf.py` to set JS file. (#77)
- `revealjs_script_conf` accepts dict types (#56)

Extra

- Change test codes from nose to py.test

4.6.12 ver 1.3.1

date
2021-07-17

base
Reveal.js 4.1.3

Fixes

- `revealjs-fragments` for paragraph contents (#71)

4.6.13 ver 1.3.0

date
2021-07-11

base
Reveal.js 4.1.3

New features

- Support some attributes of sections
- Add directive `revealjs-code-block` to line highlighting for reveal.js
- Add kebab-case directives for currently snake-case directives
 - `revealjs-slide <= revealjs_slie`
 - `revealjs-section <= revealjs_section`
 - `revealjs-break <= revealjs_break`
 - `revealjs-fragments <= revealjs_frgaments`

4.6.14 ver 1.2.1

date

2021-06-13

base

Reveal.js 4.1.3 (updated)

(Only update reveal.js)

4.6.15 ver 1.2.0

date

2021-06-06

base

Reveal.js 4.1.1 (updated)

New features

- When builder writes contents from extensions, use same of html builder

4.6.16 ver 1.1.0

date

2021-04-04

base

Reveal.js 4.1.0

New features

- Add option to add `id` attribute per sections (#59, #61)
 - Supporting label syntax of Sphinx.

Extra

- Fix dependencies for development environment
- Add `package.json` to notify updates reveal.js by dependabot

4.6.17 ver 1.0.1

date

2021-01-30

base

Reveal.js 4.1.0

Fixes

- Change order of link tags for css files (#40, #41)
- Rename test case function names for duplicated (#42, #54)

4.6.18 ver 1.0.0

date

2021-01-03

base

Reveal.js 4.1.0

Breaking changes

In this version, `sphinx-revealjs` bundle Reveal.js version 4.x, and does not supporting to work with Reveal.js 3.x.

If you want to migrate presentation source for this version, please see [migration example](#).

New features

- Using Revealjs 4.x (use 4.1.0)
 - With supporting multiple presentation management in single documentation

Drop

- Bundle and implements for Revealjs 3.x

4.6.19 ver 0.12.1

date

2020-12-12

Fixes

- Restrict effect of `revealjs_section` for only one section (PR#36)

4.6.20 ver 0.12.0

date

2020-06-21

New features

- Config variables:
 - revealjs_js_files
 - revealjs_css_files
 - revealjs_static_path

Updates

- revealjs_google_fonts use Google Fonts API version 2
- Change css selector for google-fonts

Drop

- Remove zenburn.css from default included css files
- Ignore html_js_files, html_css_files and html_static_path

4.6.21 ver 0.11.0

date
2020-04-17

Features

- Add new config variables revealjs_style_theme, revealjs_google_fonts, `revealjs_generic_font`, revealjs_script_files, revealjs_script_conf and revealjs_script_plugins
- **Breaking:** Change directive option, from config to conf in RevealjsSlide directive.

Drop

- **Breaking:** Remove config variables revealjs_theme and revealjs_theme_options.

Fixes

- Use black for formatting

4.6.22 ver 0.10.1

date

2020-04-09

Fixes

- Change bundle Reveal.js (3.9.1 -> 3.9.2)

4.6.23 ver 0.10.0

data

2020-03-25

Features

- Change bundle Reveal.js (3.8.0 -> 3.9.1)
- Add support version (3.8, author's default)

Fixes

- In development, depend by `sphinxcontrib-gtagjs`. (use in demo)

Extra

- Change license (MIT -> Apache-2.0)
- Use poetry as build environment

4.6.24 ver 0.9.0

date

2019-12-22

Fixes

- google-fonts default options is changed for not to render in template.
- Adjusting templates based by sphinx basic theme. (short breaking)
 - Enable `metatags`, `scripts` and more template values.

4.6.25 ver 0.8.0

date

2019-11-11

Features

- Add new config option `google_font` to set google-font style.

4.6.26 ver 0.7.0

date

2019-10-28

Features

- Add new directive `revealjs_fragments` to use Fragment.

4.6.27 ver 0.6.1

date

2019-09-12

Fixes

- Remove tag that refer source not exits

4.6.28 ver 0.6.0

date

2019-07-31

Features

- Add new directive `revealjs_break` to split sections.
 - Updated demo

Extra

- Add docstrings any sources. (ignore tests)
- Remove Pipenv.
- Migrate metadata and options from `setup.py` into `setup.cfg`.
- Use bumpversion for versioning

4.6.29 ver 0.5.1

date

2019-06-30

Extra

- Update Reveal.js from 3.7.0 to 3.8.0

4.6.30 ver 0.5.0

date

2018-12-31

Features

- Revealjs initialize config accept from sphinx document config
- Revealjs initialize config accept from `revealjs_slide` directive

4.6.31 ver 0.4.1

date

2018-12-21

Fixes

- `revealjs_section` directive of source apply for itself only

4.6.32 ver 0.4.0

date

2018-12-10

Features

- It can select theme per presentations.

4.6.33 ver 0.3.1

First public release on PyPI.

LICENSES

This library is licensed Apache License version 2.0.

About license of directly dependencies, please see each software projects or documentations.

- docutils:
 - <https://docutils.sourceforge.io/>
- Sphinx:
 - <https://www.sphinx-doc.org/>
 - <https://github.com/sphinx-doc/sphinx>
- Reveal.js:
 - <https://revealjs.com/#/>
 - <https://github.com/hakimel/reveal.js>

**CHAPTER
SIX**

INDICES AND TABLES

- genindex
- modindex
- search

INDEX

Symbols

:conf: (*directive option*)
 revealjs-slide (*directive*), 15
:data-XXX: (*directive option*)
 revealjs-break (*directive*), 16
 revealjs-section (*directive*), 15
:data-line-numbers: (*directive option*)
 revealjs-code-block (*directive*), 17
:google_font: (*directive option*)
 revealjs-slide (*directive*), 15
:notitle: (*directive option*)
 revealjs-break (*directive*), 16
:theme: (*directive option*)
 revealjs-slide (*directive*), 15

C

configuration value
 revealjs_css_files, 11
 revealjs_generic_font, 14
 revealjs_google_fonts, 14
 revealjs_js_files, 11
 revealjs_script_conf, 12
 revealjs_script_files, 12
 revealjs_script_plugins, 13
 revealjs_static_path, 11
 revealjs_style_theme, 12
 revealjs_use_section_ids, 12

R

revealjs_break (*directive*), 16
revealjs_css_files
 configuration value, 11
revealjs_fragments (*directive*), 17
revealjs_generic_font
 configuration value, 14
revealjs_google_fonts
 configuration value, 14
revealjs_js_files
 configuration value, 11
revealjs_script_conf
 configuration value, 12
revealjs_script_files

 configuration value, 12
revealjs_script_plugins
 configuration value, 13
revealjs_section (*directive*), 16
revealjs_static_path
 configuration value, 11
revealjs_style_theme
 configuration value, 12
revealjs_use_section_ids
 configuration value, 12
revealjs-break (*directive*), 16
 :data-XXX: (*directive option*), 16
 :notitle: (*directive option*), 16
revealjs-code-block (*directive*), 17
 :data-line-numbers: (*directive option*), 17
revealjs-fragments (*directive*), 17
revealjs-section (*directive*), 15
 :data-XXX: (*directive option*), 15
revealjs-slide (*directive*), 15
 :conf: (*directive option*), 15
 :google_font: (*directive option*), 15
 :theme: (*directive option*), 15