
sphinx-revealjs Documentation

Release 2.1.0

Kazuya Takei

Aug 27, 2022

CONTENTS

1 Basic Features	3
2 Demo	5
3 Concept and motivation	7
4 Contents	9
4.1 Setup	9
4.2 Upgrading guide	10
4.3 Configurations	13
4.4 Directives	18
4.5 Using tips	20
4.6 Contributing	23
4.7 Changelog	23
5 Licenses	37
6 Indices and tables	39
Index	41

`sphinx-revealjs` is Sphinx extension to generate Reveal.js presentation documents from **standard** reStructuredText.

**CHAPTER
ONE**

BASIC FEATURES

- Nested sections
- Speaker note
- Syntax highlight for Reveal.js (not used pygments)
- Customize slides and sections by conf.py or source reST

**CHAPTER
TWO**

DEMO

- Source: Sphinx document
- Created: Reveal.js presentation

```
=====
sphinx-revealjs
=====

.. revealjs_slide::

{
    controls: true,
    progress: true,
    history: true,
    center: true,
    transition: "slide",
    dependencies: [
        { src: "{{ pathto('_static/revealjs/plugin/notes/notes.js', 1) }}", async: true },
        { src: "{{ pathto('_static/revealjs/plugin/highlight/highlight.js', 1) }}", async: true, callback: function() {
    }
}
}

:Based version: 0.9.0
:Released: 2019-12-22

Overview
=====

What is this?
-----

Sphinx extension to build Revealjs presentation

Features
-----

.. This is reST comment. Render into speaker note section

* Convert sections from reStructuredText directly
* Select theme from default themes

Convert sections from reStructuredText directly
=====

Adjust section structure
```

sphinx-revealjs

Based version:
0.9.0

Released:
2019-12-22

**CHAPTER
THREE**

CONCEPT AND MOTIVATION

Goal of this library is to provide presentation platform for self-branding of engineer using Sphinx. Using static site hosting service, you can show own presentations to anyone.

Core motivation is that I want to play presentation by this library.

CONTENTS

4.1 Setup

4.1.1 Requirements

`sphinx-revealjs` requires Python 3.6+ and Sphinx.

Current development environment

- Python: 3.10.4
- Sphinx: 4.3.2

4.1.2 Installation

You can install `sphinx-revealjs` from PyPI.

```
$ pip install sphinx-revealjs
```

`sphinx-revealjs` specify Sphinx and docutils expressly as dependencies. You get Sphinx by this command only.

4.1.3 Configuration

`sphinx-revealjs` does not provide `revealjs` builder instead of `html` builder. To use builder, edit your `conf.py`.

```
extensions = [  
    "sphinx_revealjs",  
]
```

if you want to configure more, edit `conf.py` with seeing [*Configurations*](#).

4.1.4 Build

Run make command to build presentations. Files are generated to **revealjs** folder.

```
$ make revealjs
```

You can generate all pages as `index.html` to use `dirrevealjs`.

```
make dirrevealjs
```

4.2 Upgrading guide

4.2.1 Upgrading from 0.x to 1.x

From version 1.x, this bundle Reveal.js 4.x, and implement for it. Due it, documentations for old version does not work to build correctly.

You have to lock version, or migrate source for next version.

Configurations

revealjs_script_plugins

Reveal.js 4.x has big changes for usage of plugins from 3.x.

`sphinx-revealjs` is also adjust for this changes, and need update `revealjs_script_plugins`.

```
revealjs_script_plugins = [
    {
        "name": "RevealNotes",
        "src": "revealjs4/plugin/notes/notes.js",
        "src": "revealjs/plugin/notes/notes.js",
    },
    {
        "name": "RevealHighlight",
        "src": "revealjs4/plugin/highlight/highlight.js",
        "src": "revealjs/plugin/highlight/highlight.js",
        "options": "",
        "options": {
            "async": true,
            "callback": function() { hljs.initHighlightingOnLoad(); }
        }
    },
]
```

- Changed structure from src and options to src and name.
 - For 4.x, to use plugin for core,
add class name of it not source path,
and need to preload source by `script` tag.
 - Class name is defined in plugin source.
You need find from source or ref documents (official plugin only)
 - In adding, does not accept options for plugins.

MORE: See [Using Plugins from Reveal.js document](#)

revealjs_css_files

If you use highlight plugin and specify bundled stylesheet file, change path of stylesheet. Style files is migrated to highlight plugin folder.

- Before: revealjs/lib/css/zenburn.css
- After: revealjs4/plugin/highlight

4.2.2 Upgrading from 1.x to 2.x

From 2.x, some features are removed because splitted other extensions or duplicated behaviors. If you want to use new version by documentation using 1.x, you should upgrade project files.

Fonts

sphinx-revealjs does not support font configuration features to provide features as “Presentation tools”.

If you want to use Google Fonts

You can add CSS URL into `revealjs_css_files` directly.

```
revealjs_css_files = [
    "https://fonts.googleapis.com/css2?family=Noto+Sans+JP",
    "css/custom.css",
]
```

Example of `css/custom.css`.

```
.reveal *, .reveal h1, .reveal h2, .reveal h3, .reveal h4, .reveal h5, .reveal h6 {
    font-family: 'Noto Sans JP', sans-serif;
}
```

Use googlefonts-markup

If you want to write only font-family, use `googlefonts-markup`.

```
from googlefonts_markup import Font

revealjs_css_files = [
    Font(family_name="Noto Sans JP").css_url(),
    "css/custom.css",
]
```

Change using Google Fonts per presentations

You need to create custom theme per presentations.

```
# Define default theme
revealjs_style_theme = "black"
```

```
=====
Title
=====

... Set `revealjs-slide/theme` to override theme

... revealjs-slide:::
:theme: "css/theme-for-this-presentation.css"
```

Speaker Views

New configuration `revealjs_notes_from_comments` are defined. But, because default values is `False`, your presentation not write speaker-note when you upgrade `sphinx-revealjs`

Replace `reveajs-notes`(recommended)

You can replace `revealjs-notes` from comment-block. And you can use comment-block as COMMENT(does not write as content from source).

Before:

```
... This is 1.x style speaker-view content
```

After:

```
.. revealjs-notes::

    This is 1.x style speaker-view content
```

Configuration for compatible behaviors

You can set True `revealjs_notes_from_comments` to use behaviors of ver 1.x.

```
revealjs_notes_from_comments = True
```

Configurations

html_js_files/revealjs_js_files

sphinx-revealjs does not ref `html_js_files` as list of additional JavaScript files. It refer only `revealjs_js_files`.

You must do one of these.

- Copy needy values of `html_js_files` to `revealjs_js_files`
- Sync `html_js_files` to `revealjs_js_files` (ex: `revealjs_js_files = html_js_files`)

revealjs_use_index

sphinx-revealjs does not generate `genindex.html` (list of in vals) on default. If you want `genindex.html` for Reveal.js builder, you muse set True.

Directives

sphinx-revealjs defines kebab-cased directives only, and removed snake-cased directives. You must replace cases to run by 2.x.

Before	After
<code>revealjs_break</code>	<code>revealjs-break</code>
<code>revealjs_fragments</code>	<code>revealjs-fragments</code>
<code>revealjs_section</code>	<code>revealjs-section</code>
<code>revealjs_slide</code>	<code>revealjs-slide</code>

4.3 Configurations

sphinx-revealjs can build multiple presentations. You can configure in `conf.py` for all presentations.

4.3.1 Basic configurations

revealjs_static_path

Type
list

Default
[] (empty)

Example
["_static"]

List of static files directory (same as `html_static_path`)

revealjs_js_files

Type
list

Default

[] (empty)

Example

["custom.js"]

List of using custom css (same as `html_js_files`).

When you want to use JS that does not related revealjs, can use this.

revealjs_css_files

Type

list

Default

[] (empty)

Example

["custom.css"]

List of using custom css (same as `html_css_files`).

If you want to customize presentation by CSS, write external css and use it.

revealjs_use_index

Type

bool

Default

False

Flag that does builder generate `genindex.html` (same as `html_use_index`).

4.3.2 Style Configurations

revealjs_style_theme

Type

str

Default

black

Example

moon, custom.css

Theme name of stylesheet for Reveal.js.

- If value does not have suffix `.css`,
use bundled Reveal.js theme(included `revealjs/css/theme`).

4.3.3 Presentation Configurations

revealjs_use_section_ids

Type
boolean

Default
False

If this is set True, inject id attribute into section element (parent of headerings). This means that change format of internal links (default is numbering style).

revealjs_script_files

Type
List[str]

Default
[]

Example
["presentation.js"]

List of sources that render as script tags.

There is bundled Reveal.js script at revealjs/js/reveal.js.

Example:

```
<div>
    <!-- Presentation body -->
</div>
<!-- here!! -->
<script src="_static/revealjs/js/revealjs.js"></script>
<script src="_static/presentation.js"></script>
```

revealjs_script_conf

Type
str or dict

Default
None

Configuration of Reveal.js presentation. This value is used as options of Reveal.initialize in output files.

- If value is string type, handle as raw javascript code.
- If value is dict object, convert to json string at internal.

Example 1: case of str

```
revealjs_script_conf = """
{
    controls: false,
    transition: 'zoom',
}
"""
```

```
<div>
    <!-- Presentation body -->
</div>
<script src="_static/revealjs/js/revealjs.js"></script>
<!-- here!! -->
<script>
    let revealjsConfig = {};
    revealjsConfig = Object.assign(revealjsConfig, {
        controls: false,
        transition: 'zoom',
    });
    revealjs.initialize(revealjsConfig);
</script>
```

Example 2: case of dict

```
revealjs_script_conf = {
    "controls": False,
    "transition": "zoom",
}
```

```
<div>
    <!-- Presentation body -->
</div>
<script src="_static/revealjs/js/revealjs.js"></script>
<!-- here!! -->
<script>
    let revealjsConfig = {};
    revealjsConfig = Object.assign(revealjsConfig, JSON.parse('{"controls": false,
    "transition": "zoom"}'));
    revealjs.initialize(revealjsConfig);
</script>
```

example 1 and 2 are behaving same.

revealjs_script_plugins

Type
List[Dict]

Default
[]

List of plugin configurations. If this value is set, render `script` tag after source `script` tags.

There are bundled Reveal.js plugins at `revealjs/plugin`.

Example:

```
revealjs_script_plugins = [
    {
        "src": "revealjs4/plugin/highlight/highlight.js",
        "name": "RevealHighlight",
    },
]
```

```
<div>
    <!-- Presentation body -->
</div>
<script src="_static/revealjs/js/revealjs.js"></script>
<script src="_static/revealjs/plugin/highlight/highlight.js"></script>
<!-- here!! -->
<script>
    let revealjsConfig = {};
    revealjsConfig.plugins = [RevealHighlight,];
    revealjs.initialize(revealjsConfig);
</script>
```

revealjs_notes_from_comments

Type
boolean

Default
False

If this is set *True*, builder writes notes section from comment block.

4.3.4 Font configurations

Note: These configurations will be dropped when version 2.x.

You can use raw CSS or `googlefonts-markup` instead of these.

revealjs_google_fonts

Type
dict

Default
[]

Example
[]

List of using fonts from [Google Fonts](#). If this value is set, render `link` and `style` tags into html.

revealjs_generic_font

Type
str

Default
sans-serif

Example
serif, monospace

If you use `revealjs_google_fonts`, set last of `font-family` style.

4.4 Directives

sphinx-revealjs provides some directives to customize presence and behaviors.

4.4.1 For customize presentation

Sphinx can manage multiple documents, so that `sphinx-revealjs` can build multiple presentation slides.

If you want to configure one presentation from some, use this directive into your source.

`.. revealjs-slide::`

Write `revealjs-slide` directive on directly below of title header.

Note: Directive based customize has options less than conf based because implementation restrict.

`:theme: (string)`

Override `revealjs_style_theme`.

`:google_font: (string)`

Override `revealjs_google_fonts`, but it can specify only one.

`:conf: (JSON-string or no-value)`

Override `revealjs_script_conf`, but single line only.

Usage:

```
Presentation title
```

```
=====
```

```
.. revealjs-slide::
```

```
  :theme: moon
```

```
Section
```

```
-----
```

```
Content
```

4.4.2 For customize sections

If you want to change behavior of sections, use these directives.

`.. revealjs-section::`

To change behavior per section, write directive per section.

`:data-XXX:`

This directive can accept attribute as same as Reveal.js section tags.

Usage:

Write `revealjs-slide` directive on directly below of section title header.

```
Title
=====
Section
-----
.. revealjs-section:: :data-background-color: #009900
```

.. revealjs-break::

If you want to transition section with keeping title, `revealjs-break` can use.

Usage:

Write `revealjs-break` to point of want to split section.

```
Title
=====
Section
-----
Content 1
.. revealjs-break::
Content 2(next slide)
```

:data-XXX:

It accepts attributes as same as `revealjs-section`.

:notitle:

If it is set in directive, next section page does not display title.

4.4.3 For interactive contents

.. revealjs-code-block::

This is extends of `code-block` direcrive for presentation.

If you want to use `data-line-number` attributes in code-block.

:data-line-numbers: (string or no value)

Code highlighting pattern. See [Reveal.js document](#)

Example:

```
.. revealjs-code-block:: python
:data-line-numbers: 1

def hello():
    print("world")
```

.. revealjs-fragments::

Note: There are cases not working regular.

Inject `fragment` attribute into objects. Referer to “Fragments” from Reveal.js

Example:

Write block as directive that you want to present as fragments.

```
.. revealjs-fragments::
```

- * First
- * Second
- * Third

See [demo](#)

.. revealjs-notes::

When you write this section, inner text are as content of Speaker View.

If you write some directives on same-level, Reveal.js uses first direcive only.

Note: You must be careful for comment block when you set `revealjs_notes_from_comments` in conf.py. Reveal.js recognizes first `<aside>` element as content of speaker-view, so you may not see directive content as notes.

Example:

```
.. revealjs-notes::
```

```
This content output into <aside> element on <section>.
```

4.5 Using tips

4.5.1 Create custom theme

Added

v2.1.0

sphinx-revealjs includes SCSS sources of bundled themes. You can write custom theme from theme template of reveal.js using libsass.

Example 1: Using libsass

First, install `libsass` to compile SASS/SCSS on your environment.

```
pip install libsass
```

Write SCSS source for your theme.

```
// Use template sources from Reveal.js
@import "template/mixins";
@import "template/settings";

// Write your settings
$base03: #002b36;

// ...

@import "template/theme";

// You can write custom style too.
.reveal {
    h1, h2, h3 {
        text-transform: none;
    }
}
```

Compile source.

```
from pathlib import Path

import sass
from sphinx_revealjs.themes import get_theme_path

source = Path("_sass/custom.scss").read_text()
css = sass.compile(
    string=source,
    include_paths=[str(get_theme_path() / "static/revealjs4/css/theme")]
)
Path("_static/custom.css").write_text(css)
```

Use compiled CSS as your theme.

```
# conf.py
# If option has extension, find from static files.
revealjs_style_theme = "custom.css"
revealjs_static_path = ["_static"]
```

Example 2: sphinxcontrib-sass

You can use `sphinxcontrib-sass` to simplify.

```
pip install --find-links=https://github.com/attakei-lab/sphinxcontrib-sass/releases.  
↳sphinxcontrib-sass
```

```
# conf.py  
from sphinx_revealjs.themes import get_theme_path  
  
extensions = [  
    # .. Your extensions  
    # Add  
    "sphinxcontrib.sass",  
]  
  
sass_src_dir = "_sass"  
sass_out_dir = "_static"  
sass_targets = {"custom.scss": "custom.css"}  
sass_include_paths = [  
    get_theme_path("sphinx_revealjs") / "static" / "revealjs4" / "css" / "theme",  
]
```

When document updated, it compile scss to css.

4.5.2 Customizing design simply

When using bundled theme, you can customize design by adding custom CSS.

Example: Disable transform style in header text

Some of reveal.js bundled themes (ex: `black`) set uppercase in `text-transform` of heading texts. You can add extra custom CSS to use other settings.

Source

Listing 1: conf.py

```
revealjs_css_files = [  
    "revealjs4/plugin/highlight/zenburn.css",  
    "custom.css",  
]
```

Listing 2: custom.css

```
.reveal h1, .reveal h2, .reveal h3, .reveal h4, .reveal h5, .reveal h6 {  
    text-transform: none;  
}
```

4.6 Contributing

Thank you for interested to sphinx-revealjs.

Todo: Add USING, QUESTION and DOCUMENTATION

4.6.1 Contribute code

Local development environment

This is spec for development by author(attakei) on 2022/08/27.

- Arch Linux
- Python 3.10.x
- Using poetry
- Installed pre-commit globally

Setting up repo

After you clone forked Git repository, run commands to set up.

```
poetry install
poetry run python tools/fetch_revealjs.py
pre-commit install
```

Important: There are difference versions from Poetry and pre-commit.

4.7 Changelog

4.7.1 ver 2.1.0

date
2022-08-28

base
Reveal.js 4.3.1

Added Features

- Package includes SCSS sources of revealjs bundled-themes

Extra

- Use pre-commit

4.7.2 ver 2.0.1

date
2022-08-02

base
Reveal.js 4.3.1

Fixes

- Custom builders accept `app` and `env` (optional) in initialize function

4.7.3 ver 2.0.0

date
2022-05-31

base
Reveal.js 4.3.1

Added Features

- Directive `revealjs-notes` writes speaker-view content into presentation
- Config `reveajs_notes_from_comments` toggle if it creates speaker-view content from comment-block
 - BREAKING CHANGE: Default value is False. You must set True explicitly to use as same as ver 1.x
- Config `reveajs_use_index` toggle if it creates `genindex.html`
 - BREAKING CHANGE: Default value is False. You must set True explicitly to use as same as ver 1.x

Fixes

- Register `data-XXX` attributes into `revealjs-section` and `revealjs-break` from <https://revealjs.com/>

Deleted features

- Remove snake-cased directives
- Does not generate `search.html`

4.7.4 Old versions

Version 1.x

ver 1.5.3

date
2022-06-02

base
Reveal.js 4.3.1

Fixes

- All nodes for `sphinx-revealjs` does not write anything when none revealjs builder works.

ver 1.5.2

date
2022-04-29

base
Reveal.js 4.3.1

Fixes

- Work `revealjs-break` directive in `dirrevealjs` builder (#109)
- Inherit behavior of any nodes from `html` builder to `dirrevealjs` builder (#108)

Deprecated

Mark as deprecated(logging.warning) to drop at version 2.x (updated from v1.5.0)

- Snake-cased directive (`revealjs_slide`, `revealjs_section` and `revealjs_break`)
- CSS Font configurations (`revealjs_google_fonts` and `revealjs_generic_font`)
- Passing values from `html_js_files` to `revealjs_js_files`

ver 1.5.1

date
2022-04-21

base
Reveal.js 4.3.1

Fixes

- Add role="main" into page.html for searching by Sphinx (#102)

Misc

- Add documentation link into metadata (PyPI)

ver 1.5.0

date
2022-04-11

base
Reveal.js 4.3.1

Features

- Add dirrevealjs builder to generate all pages as index.html

Deprecated

Mark as deprecated(logging.info) to drop at version 2.x

- Snake-cased directive (revealjs_slide, revealjs_section and revealjs_break)
- CSS Font configurations (revealjs_google_fonts and revealjs_generic_font)
- Passing values from html_js_files to revealjs_js_files
- Full-support for Python 3.6.x

ver 1.4.6

date
2022-03-26

base
Reveal.js 4.3.1 (updated)

(Only update reveal.js)

ver 1.4.5

date
2022-03-06

base
Reveal.js 4.3.0 (updated)

(Only update reveal.js)

ver 1.4.4

date
2021-12-12

base
Reveal.js 4.2.1 (updated)

(Only update reveal.js)

ver 1.4.3

Date
2021-11-20

Reveal.js
v4.2.0

(None updates for features)

Extra

- Update classifiers of PyPI
 - Fix key of license
 - Add other keys

ver 1.4.2

Date
2021-11-20

Reveal.js
v4.2.0

(None updates for features)

Extra

- Update test matrix of GitHub Actions to confirm that this supports python 3.10
- Update classifiers of PyPI because test cases passed under Python 3.10 and Sphinx 4.x

ver 1.4.1

Date

2021-11-16

Reveal.js

v4.2.0 (**updated**)

Fixes

- Replace reveal.js to use right bundle version.

ver 1.4.0

Date

2021-11-13

Reveal.js

v4.2.0 (**updated**)

New features

- Add `revealjs_js_files` for `conf.py` to set JS file. (#77)
- `revealjs_script_conf` accepts dict types (#56)

Extra

- Change test codes from nose to py.test

ver 1.3.1

date

2021-07-17

base

Reveal.js 4.1.3

Fixes

- `revealjs-fragments` for paragraph contents (#71)

ver 1.3.0

date
2021-07-11

base
Reveal.js 4.1.3

New features

- Support some attributes of sections
- Add directive `revealjs-code-block` to line highlighting for reveal.js
- Add kebab-case directives for currently snake-case directives
 - `revealjs-slide <= revealjs_slie`
 - `revealjs-section <= revealjs_section`
 - `revealjs-break <= revealjs_break`
 - `revealjs-fragments <= revealjs_fragments`

ver 1.2.1

date
2021-06-13

base
Reveal.js 4.1.3 (updated)

(Only update reveal.js)

ver 1.2.0

date
2021-06-06

base
Reveal.js 4.1.1 (updated)

New features

- When builder writes contents from extensions, use same of html builder

ver 1.1.0

date
2021-04-04

base
Reveal.js 4.1.0

New features

- Add option to add `id` attribute per sections (#59, #61)
 - Supporting label syntax of Sphinx.

Extra

- Fix dependencies for development environment
- Add `package.json` to notify updates reveal.js by dependabot

ver 1.0.1

date
2021-01-30

base
Reveal.js 4.1.0

Fixes

- Change order of link tags for css files (#40, #41)
- Rename test case function names for duplicated (#42, #54)

ver 1.0.0

date
2021-01-03

base
Reveal.js 4.1.0

Breaking changes

In this version, `sphinx-revealjs` bundle Reveal.js version 4.x, and does not supporting to work with Reveal.js 3.x. If you want to migrate presentation source for this version, please see [migration example](#).

New features

- Using Revealjs 4.x (use 4.1.0)
 - With supporting multiple presentation management in single documentation

Drop

- Bundle and implements for Revealjs 3.x

Version 0.x

ver 0.12.1

date
2020-12-12

Fixes

- Restrict effect of `revealjs_section` for only one section ([PR#36](#))

ver 0.12.0

date
2020-06-21

New features

- Config variables:
 - `revealjs_js_files`
 - `revealjs_css_files`
 - `revealjs_static_path`

Updates

- `revealjs_google_fonts` use Google Fonts API version 2
- Change css selector for google-fonts

Drop

- Remove `zenburn.css` from default included css files
- Ignore `html_js_files`, `html_css_files` and `html_static_path`

ver 0.11.0

date

2020-04-17

Features

- Add new config variables `revealjs_style_theme`, `revealjs_google_fonts`, ```revealjs_generic_font```, `revealjs_script_files`, `revealjs_script_conf` and `revealjs_script_plugins`
- **Breaking:** Change directive option, from `config` to `conf` in `RevealjsSlide` directive.

Drop

- **Breaking:** Remove config variables `revealjs_theme` and `revealjs_theme_options`.

Fixes

- Use black for formatting

ver 0.10.1

date

2020-04-09

Fixes

- Change bundle Reveal.js (3.9.1 -> 3.9.2)

ver 0.10.0

data

2020-03-25

Features

- Change bundle Reveal.js (3.8.0 -> 3.9.1)
- Add support version (3.8, author's default)

Fixes

- In development, depend by `sphinxcontrib-gtagjs`. (use in demo)

Extra

- Change license (MIT -> Apache-2.0)
- Use poetry as build environment

ver 0.9.0

date

2019-12-22

Fixes

- google-fonts default options is changed for not to render in template.
- Adjusting templates based by sphinx basic theme. (short breaking)
 - Enable `metatags`, `scripts` and more template values.

ver 0.8.0

date

2019-11-11

Features

- Add new config option `google_font` to set google-font style.

ver 0.7.0

date

2019-10-28

Features

- Add new directive `revealjs_fragments` to use Fragment.

ver 0.6.1

date

2019-09-12

Fixes

- Remove tag that refer source not exists

ver 0.6.0

date

2019-07-31

Features

- Add new directive `revealjs_break` to split sections.
 - Updated demo

Extra

- Add docstrings any sources. (ignore tests)
- Remove Pipenv.
- Migrate metadata and options from `setup.py` into `setup.cfg`.
- Use bumpversion for versioning

ver 0.5.1

date
2019-06-30

Extra

- Update Reveal.js from 3.7.0 to 3.8.0

ver 0.5.0

date
2018-12-31

Features

- Revealjs initialize config accept from sphinx document config
- Revealjs initialize config accept from `revealjs_slide` directive

ver 0.4.1

date
2018-12-21

Fixes

- `revealjs_section` directive of source apply for itself only

ver 0.4.0

date
2018-12-10

Features

- It can select theme per presentations.

ver 0.3.1

First public release on PyPI.

LICENSES

This library is licensed Apache License version 2.0.

About license of directly dependencies, please see each software projects or documentations.

- docutils:
 - <https://docutils.sourceforge.io/>
- Sphinx:
 - <https://www.sphinx-doc.org/>
 - <https://github.com/sphinx-doc/sphinx>
- Reveal.js:
 - <https://revealjs.com/#/>
 - <https://github.com/hakimel/reveal.js>

**CHAPTER
SIX**

INDICES AND TABLES

- genindex
- modindex
- search

INDEX

Symbols

:conf: (*directive option*)
 revealjs-slide (*directive*), 18
:data-XXX: (*directive option*)
 revealjs-break (*directive*), 19
 revealjs-section (*directive*), 18
:data-line-numbers: (*directive option*)
 revealjs-code-block (*directive*), 19
:google_font: (*directive option*)
 revealjs-slide (*directive*), 18
:notitle: (*directive option*)
 revealjs-break (*directive*), 19
:theme: (*directive option*)
 revealjs-slide (*directive*), 18

C

configuration value
 revealjs_css_files, 14
 revealjs_generic_font, 17
 revealjs_google_fonts, 17
 revealjs_js_files, 13
 revealjs_notes_from_comments, 17
 revealjs_script_conf, 15
 revealjs_script_files, 15
 revealjs_script_plugins, 16
 revealjs_static_path, 13
 revealjs_style_theme, 14
 revealjs_use_index, 14
 revealjs_use_section_ids, 15

R

revealjs_css_files
 configuration value, 14
revealjs_generic_font
 configuration value, 17
revealjs_google_fonts
 configuration value, 17
revealjs_js_files
 configuration value, 13
revealjs_notes_from_comments
 configuration value, 17
revealjs_script_conf

 configuration value, 15
revealjs_script_files
 configuration value, 15
revealjs_script_plugins
 configuration value, 16
revealjs_static_path
 configuration value, 13
revealjs_style_theme
 configuration value, 14
revealjs_use_index
 configuration value, 14
revealjs_use_section_ids
 configuration value, 15
revealjs-break (*directive*), 19
 :data-XXX: (*directive option*), 19
 :notitle: (*directive option*), 19
revealjs-code-block (*directive*), 19
 :data-line-numbers: (*directive option*), 19
revealjs-fragments (*directive*), 19
revealjs-notes (*directive*), 20
revealjs-section (*directive*), 18
 :data-XXX: (*directive option*), 18
revealjs-slide (*directive*), 18
 :conf: (*directive option*), 18
 :google_font: (*directive option*), 18
 :theme: (*directive option*), 18